







Max 350 mm



As from 440 kgs



600 litres



Optional



HIGH-PRESSURE CLEANING

URBANJET

TAKING DRAIN CLEARANCE TO THE NEXT LEVEL

LIGHTWEIGHT

The new lightweight UrbanJet is designed to fit most compact 3.5t vans such as the VW Transporter, Ford Transit, Vauxhall Movano, MB Vito or similar sized vans. The new UrbanJet is ideally suited for unblocking of house connections and work in domestic and light commercial areas. The UrbanJet is also available with an industrial, water-cooled diesel or petrol engine to service pipes up to 350 mm.

EVERYTHING YOU NEED

The UrbanJet is supplied as a complete package, including a hydraulically driven high-pressure hose reel with 60 metres MaxFlow lightweight jetting hose and filling reel with 35 metres of NW 19 hose. The optionally included 5 or 7-channel radio remote control allows single-person operation and allows the user to control the pump (on/off), engine revs and emergency stop.

The run-dry function for low water pump protection has an override facility allowing the operator to use the hydraulic system to retrieve the hose from the drain. The UrbanJet is available with various water tanks and can be optionally equipped with a pivoting reel for maximum flexibility.

eCONTROL+ INTERFACE

Despite its affordable price, the new UrbanJet is fitted with our award winning eControl⁺ user interface with LCD display. It includes many useful features and provides a full machine status at a glance. The eControl+ system also provides the user with machine error information for quick fault diagnostics.






- Lightweight to fit most popular and compact 3.5t + vehicles
- eControl+ control panel with machine status indicators
- Hydraulically driven high-pressure hose reel as standard
- Optionally equipped with radio remote control for single-person operation

NEW PIVOTING REEL







TECHNICAL SPECIFICATIONS		
Operating range	Max 350 mm	
Engine	Kubota diesel D1105 (18.5 kW / 25 hp) or Kubota petrol water-cooled WG972 (23 kW / 30 hp)	
Fuel tank	30 litres	
Pump Rioned/Speck	Kubota diesel D1105	
	200 bar / 45 lpm 140 bar / 60 lpm	3000 psi / 10 gpm 2000 psi / 13 gpm
	Kubota petrol water-cooled WG972	
	200 bar / 55 lpm 140 bar / 70 lpm	3000 psi / 12 gpm 2000 psi / 15 gpm
Pump protection	Run-dry protection with overrun possibility	
Pressure regulation	Type Speck with automatic bypass	
Water tank	600 litres (2 x 300 litres)	
Filling reel	35 metres NW 19	
Fixed hydrant connection	Optional	
HP hose	60 metres NW 13	
HP reel	Fixed, hydraulically driven	
Control	Rioned eControl ⁺	
Weight	From 440 kgs	
Dimensions (lxwxh)	1.305 x 1.240 x 1.195 mm	
Nozzles	2 x 1/2" (1 open, 1 blind)	
Color	Blue cover, black metal frame	

OPTIONS		
Remote control	RioMote 5 or 7-channel remote control system	
RioPulse Pulsator	Pump adjustment to send the water through the hose in pulses	
Anti-freeze tank	30 litre anti-freeze tank with circulation system to protect the high-pressure pump	
Extra water tanks	2×400 litres or 4×300 litres water tanks instead of 2×300 litres	
Extra HP hose length	80 metres NW 13	
Fixed suction venturi	Suction device for filling the tanks with tanks with surface water	
Fixed hydrant connection	Fixed hydrant connection for rapidly filling the tank	
HP reel	180° swivelling, hydraulically driven	
Second HP reel	Second HP reel instead of filling reel	
RioFree mechanical freewheel HP reel	RioFree mechanical freewheel for uncoiling without resistance (only in combination with hydraulic reel)	
Electric water level control	Automatic sysytem to open and close the filling line of your machine if the water has reached its minimum or maximum level in the tank	
Accessories	Spray gun with lance	